

9000 Rotary Switches 2A 250Vac



- ▶ Rotary action switch
- ▶ Ratings up to 2A, 250V ac
- ▶ 4 position, single pole
- ▶ 90° indexed positions



2A 250Vac T85



UL 2A 250Vac, 65°C, file E45221



RoHS compliant

μ contact gap.

Technical data on pages 4 & 5.

A 4-position single pole rotary switch. All nylon construction, threaded neck and flatted 6.0mm dia. spindle. Positive detent action, 90° between index positions. Stops available to restrict rotation.

Various circuits may be obtained by changing the supply and load connections or by omission of one or two terminals. Line and loads may be connected to any terminals. Any three of the four contacts are always connected. Illustrated loads and line are for example only.

Suitable for class II appliances. Patent app.

T9000

T 9000

TERMINAL CODE FUNCTION CODE

▶ ORDER FORMAT

▶ TERMINAL	▶ FUNCTION		▶ BODY	▶ OPTIONS
<p>T</p> <p>Solder</p>	<p>9000</p> <p>Position 1 Viewed from terminal side</p>	<p>Position 2</p>	<p>Panel Cut-out</p> <p>Panel thickness 1.25 - 3.5mm</p>	<p>Rotation Stops</p> <p>Can be specified to limit the number of switching positions</p>
	<p>Position 3</p>	<p>Position 4</p>		

Dimensions (mm)

